



VTrak Ex30 SR2 Compatibility List

Supports Service Release 2

Date: 03/15/2012

VTrak Systems Covered:

- **VTrak E630f** – 3U/16-bay 8Gb Fibre to 6Gbs SAS/SATA RAID System
- **VTrak E830f** – 4U/24-bay 8Gbs SAS to 6Gbs SAS/SATA RAID System
- **VTrak J630s** – 3U/16-bay 3Gbs SAS to 6Gbs SAS/SATA Expansion JBOD System
- **VTrak J830s** – 4U/24-bay 6Gbs SAS to 6Gbs SAS/SATA Expansion JBOD System

System Versions Covered:

- **VTrak Ex30 BootLoader** – Version 0.19.0000.30 [Jan 10, 2011]
- **VTrak Ex30 Firmware** – Version 4.06.0000.01 [Nov 11, 2011]
- **VTrak Ex30 Software** – Version 4.06.0000. 01[Nov 11, 2011]
- **6Gbs VTrak Jx30s Firmware** – Version 6.13.0000.05 [Oct 26, 2011]
- **Windows PerfectPath MPIO DSM** – Version 4.00.0000.00 [WHQL Certified]

Document History

Date	Editor	Revision	Deviation
10/20/2011	Reeba Thomas	1.0	1. Initial list for VTrak Ex30 SR1 Compatibility
11/4/2011	Reeba Thomas	1.0	1. Minor edits after implementing review comments
11/16/2011	Reeba Thomas	1.1	1. Updated Release Version Number
12/20/2011	Reeba Thomas	1.2	1. Added new drives to the list
03/15/2012	Reeba Thomas	1.3	1. Added Intel 320 drives 2. Added STEC Mach16 M16ISD2-200UCU drive

DEVICE COMPATIBILITY NOTE:

Basic compatibility between the 3rd party device and Promise device has been verified in typical configurations, unless otherwise stated.

DISCLAIMERS:

Only the versions available at time of testing have been verified, as listed. Corner cases may exist depending on user configuration etc. Individual 3rd party units may exhibit problems that did not show up in through the Promise test process. Published performance is not assured with configuration deviations.

Although Promise Technology has attempted to ensure the accuracy of the content of this document; it is possible that this document may contain technical inaccuracies, typographical, or other errors. Promise Technology assumes no liability for any error in this publication, and for damages, whether direct, indirect, incidental, and consequential or otherwise, that may result from such error, including, but not limited to loss of data or profits.

Promise Technology provides this publication “as is” without warranty of any kind, either express or implied, including, but not limited to implied warranties of merchantability or fitness for a particular purpose. The published information in the manual is subject to change without notice. Promise Technology reserves the right to make changes in the product design, layout, and driver revisions without notification to its users. This version of this document supersedes all previous versions.

Operating Systems

Supported Operating Environments			
Vendor	Core Platform	Type	Notes
Microsoft	Windows Server 2008 w/SP2	x86/x64	ALUA support with PerfectPath v4.00 or later.
	Windows Server 2008 Hyper-V w/SP2	x64	ALUA support with PerfectPath v4.00 or later.
	Windows Server 2008 R2	x64	ALUA support with PerfectPath v4.00 or later.
RedHat	Enterprise Linux 5.6	x86/x64	LUN Affinity/ALUA natively supported.
	Enterprise Linux 6.0	x86/x64	LUN Affinity/ALUA natively supported.
SuSE	Linux Enterprise Server 11.1	x86/x64	LUN Affinity/ALUA natively supported.
VMware	ESX Server v4.1 Update 1	x64	LUN Affinity/ALUA natively supported.

Note: VMware has been qualified by Promise and then certified by VMware.

Fibre Channel Host Bus Adapters

Fibre Channel HBAs							
Vendor	Model	BIOS	Firmware	Fcode	Windows	Linux	VMware Tested †
Brocade	FC425	v3.0.0.0	v3.0.0.0		v3.0.0.0	v3.0.0.0	Supported
	FC825	v3.0.0.0	v3.0.0.0		v3.0.0.0	v3.0.0.0	Certified
Emulex	LightPulse LPe12000	2.12a6	2.00a4	3.10a3	2.50.007	8.3.5.44.4p	Supported
	LightPulse LPe12002	2.12a6	2.00a4	3.10a3	2.50.007	8.3.5.44.4p	Certified
	LightPulse LPe12004	2.12a6	2.00a4	3.10a3	2.50.007	8.3.5.44.4p	Supported
	LightPulse LPe1250	2.12a6	2.00a4	3.10a3	2.50.007	8.3.5.44.4p	Supported
	LightPulse LPe11000	2.12a6	2.82a4	3.10a3	2.50.007	8.3.5.44.4p	Supported
	LightPulse LPe11002	2.12a6	2.82a4	3.10a3	2.50.007	8.3.5.44.4p	Certified
	LightPulse LPe11004	2.12a6	2.82a4	3.10a3	2.50.007	8.3.5.44.4p	Supported
	LightPulse LPe1150	2.12a6	2.82a4	3.10a3	2.50.007	8.3.5.44.4p	Supported
Qlogic	SANblade QLE2560	3.00	5.04.04	3.15	9.1.9.27	8.03.07.03	Supported
	SANblade QLE2562	3.00	5.04.04	3.15	9.1.9.27	8.03.07.03	Supported
	SANblade QLE2564	3.00	5.04.04	3.15	9.1.9.27	8.03.07.03	Certified
	SANblade QLE2460	3.00	5.04.04	3.15	9.1.9.27	8.03.07.03	Supported
	SANblade QLE2462	3.00	5.04.04	3.15	9.1.9.27	8.03.07.03	Supported
	SANblade QLE2464	3.00	5.04.04	3.15	9.1.9.27	8.03.07.03	Certified
LSI	LSI7204EP	2.02.06	1.03.27	1.00.49	1.27.01	4.00.43	Supported
	LSI7404EP	2.02.06	1.03.27	1.00.49	1.27.01	4.00.43	Supported
ATTO	Celerity FC84EN	3.24	3.24		1.32	1.32	Supported
	Celerity FC82EN	3.24	3.24		1.32	1.32	Supported

† 'VMware Tested' column indicates the level of support for VMware ESX 4.1 Update 1. 'Certified' indicates the controller was fully qualified by Promise and was used in the VMware certification test process using the Workbench test suite. 'Supported' implies the controller should work at the same level as the certified model as it is based on the same driver level and some spot testing has been performed.

Fibre Channel Switches and SFPs

Fibre Channel Switches			
Vendor	Model	Ports	Firmware
Brocade	SilkWorm 200E	16x4Gb	v5.1.0
	Brocade 300	24x8Gb	6.4.1b
	Brocade 5100	40x8Gb	6.4.1b
	Brocade 5000	32x4Gb	v6.1.1
	Brocade 8000	24x10Gb FCoE/iSCSI 8x8Gb FC	v6.4.1b
Cisco	MDS 9020	20x4Gb	v2.1
	MDS 9148	48x8Gb	v5.2
	NEXUS 5010	20x10Gb FCoE/iSCSI 6x8Gb FC	v4.1(3)N2(1)
IBM	TotalStorage SAN16B-2	16x4Gb	v6.2.2c
Qlogic	SANbox 5600Q	16x4Gb	v7.4.0.22.0
	SANbox 9000 - 4Gb blade	32-128x4Gb	v7.8.0.8.0
	SANbox 9000 - 8Gb blade	32-128x8Gb	v7.8.0.8.0
	SANbox 1400	10x4Gb	v5.0.1.10
	SANbox 5802V	20x8Gb	v7.4.0.16

SFP Interoperability Matrix (Shortwave)		
Vendor	Model	Description
Apple	4Gb SFP to SFP	2.9M 4Gb SFP Copper Cable (Qlogic 4Gb and 8Gb only)
Avago	AFBR-57D7APZ	Digital Diagnostic SFP, 850 nm, 8.5/4.25/2.125 GBd Low Voltage (3.3 V) - 85°C
Brocade	57-1000012-01	Brocade 8Gb Shortwave SFP
Cisco	DS-SFP-FC8G-SW	Cisco 8Gb Shortwave SFP
Finisar	FTLF8528P2BCV	Digital Diagnostic SFP, 850 nm, 8.5/4.25/2.125 GBd Low Voltage (3.3 V) - 70°C
Finisar	FTLF8528P2BNV	Digital Diagnostic SFP, 850 nm, 8.5/4.25/2.125 GBd Low Voltage (3.3 V) - 85°C
Finisar	FTLF8524P2BNL	Digital Diagnostic SFP, 850 nm, 8.5/4.25/2.125 GBd Low Voltage (3.3 V) - 70°C
Finisar	FTLF8528P2BNV	Digital Diagnostic SFP, 850 nm, 8.5/4.25/2.125 GBd Low Voltage (3.3 V) - 85°C

Hard Disk Drives

VTrak Ex30 and Jx30 Drive Compatibility List							
Vendor	Family	Model	Part Number	Firmware	Capacity	RPM	Interface
Hitachi	Ultrastar 7K3000	HUA723020ALA640	0F12455	5C0	2000GB	7,200	6Gb/s SATA
		HUA723030ALA640	0F12456	5C0	3000GB	7,200	6Gb/s SATA
		HUS723030ALS640	0B26311	A100	3000GB	7,200	6Gb/s SAS
		HUS723020ALS640	0B26312	A100	2000GB	7200	6Gb/s SAS
	Ultrastar A7K2000	HUA722020ALA330	0F10452	3EA	2000GB	7200	3Gb/s SATA
		HUA722010CLA330	0A39289	3EA	1000GB	7200	3Gb/s SATA
		HUA722050CLA330	0F11000	3EA	500GB	7200	3Gb/s SATA
	Ultrastar 15K600	HUS156030VLS600	0B23661	A5D0	300GB	15000	6Gb/s SAS
		HUS156045VLS600	0B23662	A5D0	450GB	15000	6Gb/s SAS
		HUS156060VLS600	0B23663	A5D0	600	15000	6Gb/s SAS

VTrak Ex30 SR2 Compatibility List v1.3

Intel	710 SSD Series	SSDSA2BZ100G23	SSDSA2BZ100G23	362	100GB	SSD/MLC	3Gb/s SATA
		SSDSA2BZ200G23	SSDSA2BZ200G23	362	200GB	SSD/MLC	3Gb/s SATA
	320 SSD Series	SSDSA2CW600G3	SSDSA2CW300G3B5	362	600GB	SSD/MLC	3Gb/s SATA
		SSDSA2CW300G3	SSDSA2CW300G3B5	362	300GB	SSD/MLC	3Gb/s SATA
		SSDSA2CW160G3	SSDSA2CW160G3K5	362	160GB	SSD/MLC	3Gb/s SATA
		SSDSA2CW120G3	SSDSA2CW120G310	362	120GB	SSD/MLC	3Gb/s SATA
		SSDSA2CW080G3	SSDSA2CW080G310	362	80GB	SSD/MLC	3Gb/s SATA
	X25-E	SSDSA2SH064G101	SSDSA2SH064G101	8860	64GB	SSD/SLC	3Gb/s SATA
		SSDSA2SH032G101	SSDSA2SH032G101	8860	32GB	SSD/SLC	3Gb/s SATA
STEC	Mach16 SSD	M16ISD2-200UCU	M16ISD2-200UCU	184	200GB	SSD/SLC	3Gb/s SATA
Seagate	Constellation ES SAS Models	ST500NM0001	9YZ262-001	2	500GB	7,200	6Gb/s SAS
		ST1000NM0001	9YZ264001	2	1000GB	7,200	6Gb/s SAS
		ST2000NM0001	9YZ268-001	2	2000GB	7,200	6Gb/s SAS
		ST32000444SS	9JX248-003	6	2000GB	7,200	6Gb/s SAS
		ST31000424SS	9JX244-003	6	1000GB	7,200	6Gb/s SAS
		ST3500414SS	9JX242-003	6	500GB	7200	6Gb/s SAS
	Constellation ES2	ST33000650SS	9SM260-002	3	3000GB	7200	6Gb/s SAS
	Cheetah 15K.7	ST3600057SS	9FS066-008	8	600GB	15000	6Gb/s SAS
		ST3450857SS	9FR066-008	8	450GB	15000	6Gb/s SAS
Western Digital	RAID Edition 4	WD2003FYYS	WD2003FYYS-02W0B0	1D01	2000GB	7,200	3Gb/s SATA
		WD1503FYYS	WD1503FYYS-02W0B0	1D01	1500GB	7,200	3Gb/s SATA
Toshiba		MK1001TRKB	HDD3A02CZK51	105	1000GB	7,200	6Gb/s SAS
		MK1002TSKB	HDD3B04CZK51	MT2A	1000GB	7,200	6Gb/s SATA
		MK2001TRKB	MK2001TRKB	105	2000GB	7,200	6Gb/s SAS
		MK2002TSKB	MK2002TSKB	MT2A	2000GB	7,200	6Gb/s SATA

Hard Disk Drive APM Support Level with MAID 2.0

Supported Disk Drives with Advanced Power Management						
Vendor	Family	Firmware	Interface	VTrak MAID Support		
				Park Heads Level-1	Reduce RPM Level-2	Spin-down Level-3
Hitachi	Ultrastar A7K2000	3EA	3Gb/s SATA	YES	YES	YES
	Ultrastar A7K3000	5C0	6Gb/s SATA	YES	YES	YES
Intel	X25-E	8850	3Gb/s SATA	n/a	n/a	n/a
Seagate	Cheetah 15K.7	0008	6Gb/s SAS	YES	NO	YES
	Constellation ES	0006	6Gb/s SAS	YES	YES	YES
	Constellation ES 2	0003	6Gb/s SAS	YES	YES	YES
Western Digital	RAID Edition 4	1D01	3Gb/s SATA	YES	NO	YES

‡ Promise qualified drives will be the only supported drives for the VTrak systems. The support requirements will be derived from the drive part numbers listed above and not necessarily by the model number. Using unqualified disk drives with the system may appear to work but cannot be guaranteed for the service life.

UPS Appliances

UPS Support*	HW Rev.	APC OS	APP. Module SW
§ APC Smart-UPS 1500VA - North America	667.18.D	v3.6.1	v3.5.8
§ APC Smart-UPS 2200VA - North America	667.18.D	v3.6.1	v3.5.8
§ APC Smart-UPS 3000VA - North America	667.18.D	v3.6.1	v3.5.8

*Tested with Ex30 Initial Release

USB Flash Drives (OPAS Service Port)

Vendor**	Family	MFG Part Number	Capacity
HP	v125w	P-FD4GBHP125-EF	4GB
Pretec	i-Disk	Q3U04G	4GB

Promise Validated Applications

Validated Applications			
Vendor	Product	Version	Description
Microsoft	Microsoft Cluster Service	2008 Server	Fail-over Cluster Service
	Microsoft Cluster Service	2008 Server R2	Fail-over Cluster Service
Oracle	Lustre Filesystem	v1.8.5	Clustered Filesystem
Quantum	Stornext Filesystem	v4.0.1.1	Distributed Filesystem (over FC) Storage Consolidation Heterogenous Windows/Linux/Mac environments Distributed LAN Clients (over Ethernet)
	Stornext Storage Manager	v4.0.1.1	Storage Tiering Archiving Data Deduplication Replication
RedHat	Global Filesystem	GFS2	Clustered Filesystem
	RH Cluster	RHEL 5.6 and 6	Fail-over Cluster Service
Symantec	Storage Foundation (for Windows)	v5.1 SP2	VERITAS Volume Management VERITAS Cluster Service (VCS)

§ The above UPS models were fully validated for use with a properly configured VTrak Ex30 system. For other regions that use different power sources, such as Japan, using the APC Smart-UPS equivalent will be supported.

** There is a large variety of USB Flash Drive vendors to select from on the market. The Promise qualification team selected only a handful to represent only a sampling of available Flash Drives. The above list shows the drives that have passed a rigorous read/write/discovery test process are deemed worthy of use out-of-the-box. There were other USB Flash drives that did not function properly out-of-the-box, and required a partition and format in order to use them.

Promise Validated Browsers for WebPAM PROe

Validated Web Browsers for Ex30 WebPAM PROe	
Product	Version
Internet Explorer	8.0.7600.16385
Safari for Mac	5.1
Safari for Windows	5.1
Mozilla Firefox for Windows	4.0.1
Mozilla Firefox for RHEL	4.0.1
Mozilla Firefox for SLES 11.1	4.0.1

♠ End of Report ♠