Promise-Linux-MPIO

Multipath Driver

Promise-Linux-MPIO 0.0.0.14
Release Notes

For use with:

E-Class SR6.3 Release (10.18.2270.00) or later

A-Class SR3.3 Release (1.16.0000.00) or later

E-5000 SR1 Release (11.03.0000.00) or later

EFA5310 FCS Release (11.03.0000.00) or later

R-2000 SR2.5 Release (1.05.0000.12) or later

Version 0.01

The Promise Linux MPIO provides a promise.sh scripts to install/uninstall the multipath configuration file.

The following Linux OS's are supported:

Vendor	Platform	Note
RedHat	Enterprise Linux 5.10 Enterprise Linux 5.11	
	Enterprise Linux 6.2 Enterprise Linux 6.3 Enterprise Linux 6.4 Enterprise Linux 6.5 Enterprise Linux 6.6 Enterprise Linux 6.7 Enterprise Linux 6.8	
	Enterprise Linux 7.0 Enterprise Linux 7.2	
SUSE	SLES 11 SP1	Need Kernel: 2.6.32.27-0.2.2 or newer
	SLES 11 SP2	
	SLES 11 SP3	Need Kernel:3.0.101-0.47.57 or newer
	SLES 11 SP4	
	SLES 12 SP1	

Instructions on the installation and use of the Promise-Linux-MPIO can be found in the **Appendix** of the **Promise E-Class Product** manual.

Changes since the Promise-Linux-MPIO 0.0.0.13 Release

Ref. #	Description
234050	The local disk is automatically added to the blacklist in multipath.conf for OS version is SUSE 12 or newer version.
237988	Fixed a bug where the uninstalling Promise-Linux-MPIO on the Suse 12 sp1 host results in maintenance mode.
237862	Fixed a bug where all LD's multipath will be "active ready running" when creating more than 14 LDs on Sles 12 SP1.